



(19)

(11) Publication number:

59078918 A

Generated Document.

## PATENT ABSTRACTS OF JAPAN

(21) Application number: 57186865

(51) Intl. Cl.: C01B 33/02

(22) Application date: 26.10.82

(30) Priority:

(43) Date of application  
publication: 08.05.84(84) Designated contracting  
states:

(71) Applicant: MITSUI TOATSU CHEM INC

(72) Inventor: KITAGAWA YORIHISA  
HIROSE ZENKO  
ISOTANI KAZUYOSHI  
ASHIDA YOSHINORI

(74) Representative:

**(54) FORMATION OF  
AMORPHOUS SILICON  
FILM WITH WIDE BAND  
GAP**

(57) Abstract:

**PURPOSE:** To form the titled amorphous silicon (a-Si) film with satisfactory control efficiency in the manufacture of an a-Si film by a chemical vapor deposition (CVD) method by adding a specified amount of ammonia (deriv.) to a gaseous starting material.

CONSTITUTION: Ammonia (deriv.) represented by formula I and/or hydrazine (deriv.) represented by formula II is used. In the formulae each or R1WR7 is H, alkyl or aryl. A substrate is placed in a decomposition furnace, silane of higher order represented by formula III (where n is 2) such as disilane or trisilane is introduced into the furnace optionally together with an inert gas such as nitrogen, and the silane is thermally decomposed at about 250W600°C to deposit an a-Si film on the substrate. At this time, said ammonia (deriv.) and/or hydrazine (deriv.) is added to the silane by an amount satisfying relation represented by formula IV [where N is the amount of nitrogen in the ammonia (deriv.) and/or hydrazine (deriv.), and Si is the amount of silicon in the gaseous silane] to form an a-Si film with about 1.6W2.5eV band gap.

COPYRIGHT: (C)1984,JPO&Japio



